

◆ LRC-1 Smart Lifter Remote

The LRC-1 Smart Lifter Remote is designed to be used with the LLT-1 Smart Light Lifters. Its plug & play feature enables users to easily install and operate the light lifter(s) from a distance, and program the LLT-1 light lifters maximum and minimum range limits. Simple Up and Down manual operation is accomplished using two push-buttons on the LRC-1.

The LRC-1 Lifter Remote can also be connected with the Hydro-X Pro for advanced features such as lifter-group control and more.



LRC-1 Smart Lifter Remote

◆ Specifications

Power Input

| | |
|----------|---------------------|
| Voltage | 110-240 V, 50/60 Hz |
| Amperage | 0.1A |

Product Dimensions

| | |
|--------|---|
| Size | 2.56" / 65 mm(L) x 5.52" / 140 mm(W) x 1.97" / 50 mm(H) |
| Weight | 0.66 lbs / 0.3 kg |

Package Content

| | |
|--------------------------------------|------|
| ThinkGrow Smart Light Remote (LRC-1) | 1 pc |
| ECS-9 Signal Cable | 1 pc |



Working Environments

| | |
|-------------|------------------|
| Temperature | 32-104° / 0-40°C |
| Humidity | ≤90% |

Packaging Dimensions and G.W.

| | |
|--------|---|
| Size | 5.12" / 130mm(L) x 7.36" / 187mm(W) x 3.46" / 88mm(H) |
| Weight | 1.33 lbs / 0.6 kg |

◆ Link Up

