




AK800 PRO® Series

Full-spectrum, high-intensity

blues and reds for full-cycle

growth



GPS-AK-800-PRO

buy another HPS bulb again. The Grow Pros AK800 Pro is a long-lasting, easy-to fixture perfect for long-term exponential growth of your plants and your business

- upplemental green house lighting

FEATURES & BENEFITS

Compact, Easy to

Install: Low-profile 4"

depth compared to 7"

width of HPS grow light

- Proven to be 35% more efficient.
- Uniform and widespread light distribution equal to DE HPS fixtures light spread while providing deeper light penetration into the canopy.
- Multiple fixtures can be daisy-chained and syned using 0-10v dimming controllers to maintain uniform dynamic light levels . throughout the full growth cycle.
- A single-tier 1:1 HPS replacement LED grow light that will match the light output and yield of HPS with greater efficiency • for greater savings over time.
- Built to withstand the elements, our product boasts an IP65

waterproof rating for added durability. Proven to be 35% more effective than HPS grow lights at up to 2.7 µmol/J

> Uniform, widespread distribution equal to HPS light throw while providing deeper penetration over the canopy

Multiple fixtures can be daisy-chained and synced using a single power supply for universal control to maintain uniform, dynamic light levels throughout the full growth cycle

A single-tier 1:1 HPS replace

performance of AK800 LED

savings over time

grow light matches HPS with greater efficiency for greater

ment LED grow light, meaning

A PPF of 2150 µmols for higher efficiency while requiring less fixtures to achieve optimal output

UNDER PROPER GROW CONDITIONS, MONEY CAN BE GAINED BACK IN AN AVERAGE OF 6-8 MONTHS

Address: 4833 Lanier Road, Chino, CA 91710

Tel: (800) 383-6200 | **Email:** info@wegrowpros.com



LED LIGHTING SOLUTION FOR COMMERCIAL, INDOOR, AND GREENHOUSE APPLICATIONS

TECHNICAL SPECIFICATIONS	
WATTAGE	800W
INPUT VOLTAGE	120V-277V
CONTROLLER	TrolMaster Hydro-X + LMA14 (26 Fixtures)
CONTROL	0-10V dimming (0-100%)
DAISY CHAIN PORT	RJ12
THD	20%
SURGE PROTECTION	L/N-PE: 10kV, L-N: 6kV
WORKING TEMPERATURE	-40°F ~ 122°F
IP RATING	IP65
SPECTRUM	Full Spectrum
WARRANTY	7 year limited
	<u> </u>

-		١Ŧ		n	Α	n
п		٩I.	ш	U	А	U
	_		_	_	-	_


HEAT LOAD PER FIXTURE	2729.71 BTU
-----------------------	-------------

STANDARD POWER ELECTRICAL DATA

AC VOLTAGE	120V	208V	240V	277V
AC CURRENT	6.8A	3.9A	3.5A	3.0A
AC POWER	826W	808W	800W	798W
POWER FACTOR	0.996	0.99	0.98	0.96

PERFORMANCE DATA PPF 2150 μmol/s PPE 2.7 μmol/J

SPECTRAL DISTRIBUTION




WHAT'S IN THE BOX

- 1x AK800 Pro
- 1x 12ft power cord
- 1x 240V to 120V adapter
- 1x RJ12 Data cable
- 1x Pair Mounting Hangers
- 1x Pair Unistrut Hooks

PPFD READING

30" Height @ MAX Power								
■ 4'X4' ■ 3'X3' ■ 2'X2' ■ 1'X1'								
535		679		780		677		529
	951						923	
622		1002		1124		1021		633
			1103		1105			
671	1207	1402		1204		1398	1202	669
			1112		1108			
625		1017		1130		1018		632
	937						931	
532		685		779		687		531

DIMENSIONS



GROSS WEIGHT: 35 lbs

Address: 4833 Lanier Road, Chino, CA 91710

Tel: (800) 383-6200 | **Email:** info@wegrowpros.com