

# TS-2

## Thermostat Station

The TS-2 thermostat stations is designed to replace a thermostat connected to a standard HVAC unit. The TS-2 can be used to control most HVAC systems including heat pump and multi-stage HVAC systems. The TS-2 is wired to the HVAC system using the same low-voltage thermostat cable, and has the standard color-coded wiring as most thermostats. The Hydro-x allows separate Day and Night settings for each of up to (4) TS modules, so multiple HVAC systems can be controlled by a single Hydro-X system. The TS-2 also has an adjustable delay time for each HVAC systems being activated. That minimizes high start-up (inrush current) and allows up to 4 HVAC systems to be safely controlled.



## Specifications

### TS-2

#### Input Voltage

Input Voltage 12 VAC

#### IP Rating

IP Rating IP20

#### Maximum Current

Maximum Current 0.1A

#### Working Environments

Temperature 32-122°F (0-50°C)

Humidity ≤90%

#### Package Dimensions

Size 6.30" / 160mm(L) x 3.39" / 86mm(W) x 3.39" / 86mm(H)

#### Package Contents

Thermostat Station 1pc

16ft RJ12 Cable 1pc

4ft RJ12 Cable 1pc

T-shaped Splitter 1pc

#### G.W. per pack

G.W. per pack 0.40kgs

#### Cetifications

Cetifications ETL/FCC

## Link Up

### TS-2

#### CONNECTION DIAGRAM

