

OA6-24

24V Control Board

The OA6-24 control board is designed to control multiple 24vac solenoid valves.

It provides an easy and efficient method to control up to 6 valves ... each with individual timer settings. Up to 5 OA6-24 can be connected to a single Aqua-x providing a maximum of 30 individually controlled outputs to connect to your solenoid valves.

The Aqua-x can also provide a "master pump link" by using a DSP-1 along with the OA6-24. Connecting a DSP-1 to the OA6-24 provides an automatic "pump link" between the DSP-1 and the OA6-24. When any of the 24vac irrigation zones are activated on the OA6-24, the DSP-1 will automatically turn on the pump.



Specifications

OA6-24

Input Voltage

Voltage	110-240 VAC
---------	-------------

Max Input Current

Holding Current	0.2A
Inrush Current	400ma

Package Content

24V Control Board	1pc
16ft RJ12 Cable	1pc

Working Environments

Temperature	32°-122°F (0-50°C)
Humidity	≤90%

Max Output Current

Voltage/Current	24VAC/0.2A per output
-----------------	-----------------------

Package Dimensions

Size	10.83" /275mm(L) x 6.46" /164mm(W) x 1.58 /40mm(H)
Gross Weight	1.34lbs /0.61kg

Link Up

OA6-24

CONNECTION DIAGRAM

