

DSP-2

240V Program Device Station

The TrolMaster DSP-2 Program Device Station (timer module) works like a multi-function timer. The DSP-2 allows the user to easily connect any device that needs to be controlled by TIME to the Hydro-X. Any device that is 10-amps at 240 volts or less can be controlled by the DSP-2.



Specifications

DSP-2

Input Voltage

Voltage 100-240V~, 50/60Hz

Output Current

Current 10A

Output Voltage

Voltage 100-240V~, 50/60Hz

Working Environments

Temperature 32-122°F (0-50°C)

Humidity ≤90%

Package Content

240V Program Device Station 1pc

16ft RJ12 Cable 1pc

4ft RJ12 Cable 1pc

RJ12 T-Splitter 1pc

Package Dimensions

Size 3.35"/85mm (L) x
3.15"/80mm (W) x
3.54"/90mm (H)

Gross Weight 12.0oz /340g

LED Indicator Status

LED Indicator	Module Status
Fast Blinking Green	Module is not addressed to the main controller, OR module does not have a good connection to the main controller. *Note: Press the small address/link button on the module when first installed.
Slow Blinking Green	Module is addressed and connected to the main controller, and is currently turned OFF.
Solid Green	Module is addressed, connected, and currently turned ON.
Blinking Red	Module is overloaded. Reset the overload by unplugging the module from powersource .

Link Up

DSP-2

CONNECTION DIAGRAM

(HCS-1/HCS-2/HCS-3/NFS-1/NFS-2)

